UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/015,926	12/10/2001	Rajeev Krishnamurthi	010121	5845

23696   7590   12/03/2009
QUALCOMM INCORPORATED
5775 MOREHOUSE DR.
SAN DIEGO, CA 92121

EXAMINER
AHMED, SALMAN

ART UNIT	PAPER NUMBER
2476	

NOTIFICATION DATE	DELIVERY MODE
12/03/2009	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

us-docketing@qualcomm.com
kascanla@qualcomm.com
nanm@qualcomm.com

	Application No.	Applicant(s)
	10/015,926	KRISHNAMURTHI ET AL.
Office Action Summary	Examiner	Art Unit	
	SALMAN AHMED	2476	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on _14 September 2009_.

2a) ☐ This action is **FINAL.** 2b) ☒ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) _1,2 and 5-68_ is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) _1,2 and 5-68_ is/are rejected.

7) ☒ Claim(s) _14-23, 54 and 55_ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☒ The drawing(s) filed on _12/10/2001_ is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☐ All b) ☐ Some * c) ☐ None of:

      1. ☐ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date _____.

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 103

1.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

2.   This application currently names joint inventors. In considering patentability of

the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of

the various claims was commonly owned at the time any inventions covered therein

were made absent any evidence to the contrary. Applicant is advised of the obligation

under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was

not commonly owned at the time a later invention was made in order for the examiner to

consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g)

prior art under 35 U.S.C. 103(a).

3.   Claims 1 and 2 are rejected under 35 U.S.C. 103(a) as being unpatentable over

Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of

Walding (US PAT 6031845).

        In regards to claim 1, Malmivirta teaches receiving a first message having

included therein test settings (column 7 lines 11-13, First, the test equipment sends a

test loop closing command related to the data channel, which command can be called

CLOSE_Multi-slot_loop_CMD. The closing command may include an identifier on the

basis of which the mobile station knows that the loop is a G loop) selected from among

a plurality of possible test settings (column 7 lines 2-10, column 8 lines 30-36, first

discussed a case where the test equipment wants the mobile station to loop back the

downlink data transmitted on the data channel after demodulation and decryption, i.e.

from point 305 to point 309 as depicted by arrow 332, referring to markings in FIG. 3.

For simplicity, this test loop can be called the G loop. As an example, let us particularly

consider a case where the data channel to be tested is a HSCSD channel, i.e. one in

which the data can be located in more than one timeslot in the radio frame. Such a

channel may also be called a multi-slot channel. Next it will be considered a case where

the test equipment wants the mobile station to loop back the downlink data transmitted

on the data channel after demodulation, decryption and channel decoding, i.e. from

point 327 to point 330, as depicted by arrow 333 in FIG. 3. For simplicity, this test loop

can be called the H loop. Let the data channel to be tested be a HSCSD channel) for

one or more channels comprising a reverse traffic channel (column 7 lines 58-60,

When the G loop is closed the mobile station loops in principle the information bits of

every burst received on the downlink data channel back to a certain uplink burst), one or

more auxiliary channels, or a combination thereof, wherein the test settings selected

comprise indications for configuring the reverse traffic channel, one or more auxiliary

channels, or a combination thereof and indications of loop back packet transmission

procedures to be performed during testing (column 7 lines 2-19, first discussed a case

where the test equipment wants the mobile station to loop back the downlink data

transmitted on the data channel after demodulation and decryption, i.e. from point 305

to point 309 as depicted by arrow 332, referring to markings in FIG. 3. For simplicity,

this test loop can be called the G loop. As an example, let us particularly consider a

case where the data channel to be tested is a HSCSD channel, i.e. one in which the

data can be located in more than one timeslot in the radio frame. Such a channel may

also be called a multi-slot channel. First, the test equipment sends a test loop closing

command related to the data channel, which command can be called CLOSE_Multi-

slot_loop_CMD. The closing command may include an identifier on the basis of which

the mobile station knows that the loop is a G loop. Alternatively, it can be specified that

if the CLOSE_Multi-slot_loop_CMD message does not include any particular identifier, it

orders the closing of the G loop); configuring the one or more channels based on the

selected test settings in the first message; receiving test packets via a forward traffic

channel; transmitting loop back packets via the reverse traffic channel if indicated by the

selected test settings, wherein the loop back packets comprise data for the received test

packets (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been

closed the test equipment can start sending test data. Testing is preferably carried out

such that the test equipment generates test bursts in which the information bits contain

desired "raw data", i.e. bit combinations the reception of which is to be examined.

Functionally, data transmission and reception occur on the physical protocol level called

Layer 1. When the G loop is closed the mobile station loops in principle the information

bits of every burst received on the downlink data channel back to a certain uplink burst.

It is here assumed bursty transmission. The same principle can easily be generalized

to apply to a situation in which the transmission is continuous; this concerns especially

the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment) and transmitting data via the one or more auxiliary channels if indicated by the selected test settings to test the one or more auxiliary channels (column 9 lines 7-24, Above it was said that the mobile station loops all the received data back uplink after the closing of the test loop. However, this is just a general principle. Data channels typically may be asymmetric between the uplink and downlink directions, i.e. a multi-slot channel, for example, may have more downlink timeslots than uplink timeslots per frame. To take this into account, advantageous operation both in the G loop case and H loop case includes two alternative mechanisms, and the test equipment can indicate in its CLOSE_Multi-slot_loop_CMD message which one of the mechanisms is activated. According to the first mechanism, the mobile station loops the data received in a given downlink timeslot back to a certain timeslot of the uplink channel which in HSCSD is called the main uplink slot and in GPRS the uplink PACCH timeslot (i.e. auxiliary channels). The downlink timeslot the looping back of which is thus specified is called timeslot X. The invention does not limit the specification of timeslot X).

Malmivirta does not explicitly teach signaling data is sent via a auxiliary channel.

Walding in the same field of endeavor teaches the overhead channel (i.e. auxiliary channel) is provided for carrying control information (i.e. signaling packets) used to establish and maintain the downlink and uplink communication paths (column 1 lines 48-50).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of signaling data being sent via auxiliary channel as suggested by Walding. The motivation is that (as suggested by Walding, column 1 lines 48-50) the overhead channel (i.e. auxiliary channel) is provided for carrying control information (i.e. signaling packets) used to establish and maintain the downlink and uplink communication paths. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 2 Malmivirta teaches each loop back packet includes data descriptive of one or more test packets (column 8 lines 51-62, the operation according to the H loop differs from that of the G loop in that as channel decoding has been performed before the data are looped back uplink, the mobile station is able to examine whether the received data frames contain errors that are revealed by means of checksums included in the data frames. The contents of all error-free received data frames are looped back to uplink data frames belonging to the same data channel and those uplink data frames are fed to the channel encoder. If the mobile station detects an erroneous data frame it notifies the test equipment e.g. by filling the appropriate

uplink data frame with zeroes before the uplink data frame is fed to the channel encoder).

4.   Claims 32 and 33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Walding (US PAT 6031845) and Gillespie (US PAT 6014377).

        In regards to claims 32 and 33, Malmivirta teaches receiving a first message having included therein test settings (column 7 lines 11-13, First, the test equipment sends a test loop closing command related to the data channel, which command can be called CLOSE_Multi-slot_loop_CMD. The closing command may include an identifier on the basis of which the mobile station knows that the loop is a G loop) selected from among a plurality of possible test settings (column 7 lines 2-10, column 8 lines 30-36, first discussed a case where the test equipment wants the mobile station to loop back the downlink data transmitted on the data channel after demodulation and decryption, i.e. from point 305 to point 309 as depicted by arrow 332, referring to markings in FIG. 3. For simplicity, this test loop can be called the G loop. As an example, let us particularly consider a case where the data channel to be tested is a HSCSD channel, i.e. one in which the data can be located in more than one timeslot in the radio frame. Such a channel may also be called a multi-slot channel. Next it will be considered a case where the test equipment wants mobile station to loop back the downlink data transmitted on the data channel after demodulation, decryption and channel decoding, i.e. from point 327 to point 330, as depicted by arrow 333 in FIG. 3. For simplicity, this

test loop can be called the H loop. Let the data channel to be tested be a HSCSD

channel) for <u>one</u> or more channels comprising a reverse traffic channel (column 7 lines

58-60, When the G loop is closed the mobile station loops in principle the information

bits of every burst received on the downlink data channel back to a certain uplink burst),

one or more auxiliary channels, or a combination thereof, wherein the test settings

selected comprise indications for configuring the reverse traffic channel, one or more

auxiliary channels, or a combination thereof and indications of loop back packet

transmission procedures to be performed during testing (column 7 lines 2-19, first

discussed a case where the test equipment wants the mobile station to loop back the

downlink data transmitted on the data channel after demodulation and decryption, i.e.

from point 305 to point 309 as depicted by arrow 332, referring to markings in FIG. 3.

For simplicity, this test loop can be called the G loop. As an example, let us particularly

consider a case where the data channel to be tested is a HSCSD channel, i.e. one in

which the data can be located in more than one timeslot in the radio frame. Such a

channel may also be called a multi-slot channel. First, the test equipment sends a test

loop closing command related to the data channel, which command can be called

CLOSE_Multi-slot_loop_CMD. The closing command may include an identifier on the

basis of which the mobile station knows that the loop is a G loop. Alternatively, it can be

specified that if the CLOSE_Multi-slot_loop_CMD message does not include any

particular identifier, it orders the closing of the G loop); configuring the one or more

channels based on the selected test settings in the first message; receiving test packets

via a forward traffic channel; transmitting loop back packets via the reverse traffic

channel if indicated by the selected test settings, wherein the loop back packets comprise data for the received test packets (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment) and transmitting data via the one or more auxiliary channels if indicated by the selected test settings to test the one or more auxiliary channels (column 9 lines 7-24, Above it was said that the mobile station loops all the received data back uplink after the closing of the test loop. However, this is just a general principle. Data channels typically may be

asymmetric between the uplink and downlink directions, i.e. a multi-slot channel, for example, may have more downlink timeslots than uplink timeslots per frame. To take this into account, advantageous operation both in the G loop case and H loop case includes two alternative mechanisms, and the test equipment can indicate in its CLOSE_Multi-slot_loop_CMD message which one of the mechanisms is activated. According to the first mechanism, the mobile station loops the data received in a given downlink timeslot back to a certain timeslot of the uplink channel which in HSCSD is called the main uplink slot and in GPRS the uplink PACCH timeslot (i.e. auxiliary channels). The downlink timeslot the looping back of which is thus specified is called timeslot X. The invention does not limit the specification of timeslot X).

Malmivirta does not explicitly teach signaling data is sent via a auxiliary channel.

Walding in the same field of endeavor teaches the overhead channel (i.e. auxiliary channel) is provided for carrying control information (i.e. signaling packets) used to establish and maintain the downlink and uplink communication paths (column 1 lines 48-50).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of signaling data being sent via auxiliary channel as suggested by Walding. The motivation is that (as suggested by Walding, column 1 lines 48-50) the overhead channel (i.e. auxiliary channel) is provided for carrying control information (i.e. signaling packets) used to establish and maintain the downlink and uplink communication paths. Known work in one field of endeavor may prompt variations of it for use in either the same field

or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Walding do not explicitly teach testing Auxiliary control channel.

Gillespie in the same or similar field of endeavor teaches testing Auxiliary control channel (column 5 lines 55-58).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Walding's system/method by incorporating the steps of testing Auxiliary control channel as suggested by Gillespie. The motivation is that such method enables the system to diagnose all channels of communication for performance, reliability and interference among other things; thus making the system optimum. Known work (i.e. diagnose all channels) in one field of endeavor (Gillespie prior art) may prompt variations of it for use in either the same field or a different one (Malmivirta and Walding prior art) based on design incentives (i.e. performance, reliability and interference) or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

5.   Claim 34 is rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Walding (US PAT 6031845), Gillespie (US PAT 6014377) and Gopalakrishnan et al. (US PAT 7110466, hereinafter Gopalakrishnan).

In regards to claim 34 Malmivirta, Walding and Gillespie teach all the limitations of claim 32, but do not explicitly teach auxiliary channels comprise at least one of an acknowledgment (ACK) channel and a data rate control (DRC) channel

Gopalakrishnan in the same field of endeavor teaches control channel (auxiliary channel) being DRC channel (column 1 lines 42-43).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Walding and Gillespie's system/method by incorporating the steps of control channel being DRC channel as suggested by Gopalakrishnan. The motivation is that (as suggested by Gopalakrishnan, column 1 lines 42-48) the pilot/DRC channel is transmitted by the mobile to provide the base station with a pilot signal that the base station uses to reliably demodulate other transmissions from the mobile to the base station and further the pilot/DRC is also used to provide the base station with data rate request information from the mobile to efficiently control transmission rate. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

6.   Claims 35-38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Walding (US PAT 6031845), Gillespie (US PAT 6014377) and Numminen et al. (US PAT 6687499, hereinafter Numminen).

In regards to claim 35-38 Malmivirta, Walding and Gillespie teach all the limitations of claim 32, but do not explicitly teach first message includes a test setting for a particular bit value to be transmitted on an acknowledgment (ACK) channel; the first message includes a test setting for a particular value to be transmitted on a data rate control (DRC) channel; the first message includes a test setting for a particular cover to be used for a data rate control (DRC) channel; the first message includes a test setting indicative of maintenance of a test mode in event of a connection closure or a lost connection.

In regards to claims 35-37 Numminen in the same or similar field of endeavor teaches the first message includes a   test setting for a particular bit value to be transmitted on an acknowledgment (ACK) channel (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) or the first message includes a test setting (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile

station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) for a particular value to be transmitted on a data rate control (DRC) channel or the first message includes a test setting (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) for a particular cover to be used for a data rate control (DRC) channel (column 6 lines 20-61). In regards to claim 38 Numminen in the same or similar field of endeavor teaches the first message includes a test setting indicative of maintenance of a test mode in event of a connection closure or a lost connection (column 7 lines 18-20, So test mode means

that the mobile station to be tested is instructed to maintain a connection on a certain

transmission channel. The mobile station is kept in the test mode by Layer 3 signaling).

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta, Walding and Gillespie's system/method by

incorporating the steps of first message includes a test setting for a particular bit value

to be transmitted on an acknowledgment (ACK) channel; the first message includes a

test setting for a particular value to be transmitted on a data rate control (DRC) channel;

the first message includes a test setting for a particular cover to be used for a data rate

control (DRC) channel; the first message includes a test setting indicative of

maintenance of a test mode in event of a connection closure or a lost connection as

suggested by Gopalakrishnan. The motivation is that by designating various bits to

identify various settings for various channels for testing, system can reliably and

seamlessly perform desired testing of desired channels. Known work in one field of

endeavor may prompt variations of it for use in either the same field or a different one

based on design incentives or other market forces/market place incentives if the

variations are predictable to one of ordinary skill in the art.

7.   Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of

Walding (US PAT 6031845) and Funk et al. (US PAT 6766164), hereinafter referred to

as Funk.

In regards to claim 5, Malmivirta teaches a memory communicatively coupled to a digital signal processing device (DSPD) (column 6 lines 57-59) and implicitly teaches loopback packet being formed for particular time interval (column 7 lines 28-35, the mobile station closes the test loop in a certain period of time from the sending of the acknowledge. Compatibility with certain functions specified earlier may require that a certain value be specified for said period of time. In the GSM system an advantageous value for said period of time is one so-called reporting period, i.e. the duration of a block on the SACCH channel, which corresponds to the length of 104 radio frames) and in view of Walding teach all the limitations of claim 1 above.

Malmivirta and Walding do not explicitly teach test packet is formed for each particular time interval.

Funk in the same field of endeavor teaches test packets being formed for particular time interval (column 3 lines 61-67).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Walding's method by incorporating one loop back packet being formed for each particular time interval as taught by Funk. The motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

8.   Claims 6-8, 10-13 and 24-28 and are rejected under 35 U.S.C. 103(a) as being

unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as

Malmivirta in view of Mawhinney et al. (US PAT 5898674, hereinafter Mawhinney) and

Brady (US PAT 3922508), hereinafter referred to as Brady.

         In regards to claims 6 and 10, Malmivirta teaches *receiving a first data*

transmission comprising test packets of known test data via a first channel (column 7

lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test

equipment can start sending test data. Testing is preferably carried out such that the

test equipment generates test bursts in which the information bits contain desired "raw

data", i.e. bit combinations the reception of which is to be examined. Functionally, data

transmission and reception occur on the physical protocol level called Layer 1. When

the G loop is closed the mobile station loops in principle the information bits of every

burst received on the downlink data channel back to a certain uplink burst. It is here

assumed bursty transmission. The same principle can easily be generalized to apply to

a situation in which the transmission is continuous; this concerns especially the testing

of mobile stations in systems utilizing the code division multiple access (CDMA)

method. In the exemplary GSM system each burst has 114 information bits to loop

back, excluding the so-called stealing flags. Preferably the loopback does not depend

on the contents of the so-called midamble of the received downlink bursts. In uplink

bursts the mobile station uses the midamble that it would use anyway. The test

equipment receives the uplink bursts sent by the mobile station and demodulates and

decrypts them so that the information bits in a received burst can be processed by the

test equipment) *and transmitting the second data transmission via a second channel* (column 7 lines 58-60, when the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst).

Malmivirta does not explicitly teach *identifying parameter values descriptive of the test packets received in the first data transmission, wherein the parameter values for each test packet comprise at least one of a serving sector from which the test packet was received, a sequence number of the test packet, and a length of the test packet; forming a second data transmission comprising the identified parameter values for test packets received.*

Mawhinney in the similar field of endeavor teaches *identifying parameter values descriptive of the test packets received in the first data transmission during the observation interval, wherein the parameter values for each test packet comprise at least one of a serving sector from which the test packet was received, a sequence number of the test packet, and a length of the test packet; forming a second data transmission comprising the identified parameter values for test packets received* (Figure 5 sequence number field, column 3 lines 38-53, column 11 lines 45-60, lines column 12 lines 1-15, column 4 lines 44-47, the testing means have a transmitter means for transmitting the test sequence to the second device across the diagnostic channel. A receiver is associated with the second device for receiving and identifying the test sequence transmitted by the first device. Responding means associated with the second device for responding to the test sequence, the responding means being

configured to transmit its response over the diagnostic channel, back to the first device. Finally, evaluating means are associated with the first device for identifying the response. The specific operation of the particular elements, such as the responding means and the evaluating means still necessarily vary, depending upon the particular diagnostic test being executed. For example, the operation of the elements, while executing a diagnostic pattern test, will be different than when executing a loopback test. A loopback test is typically run in conjunction with a send pattern and/monitor pattern command. When loopback is active on a virtual circuit, all frames received on the diagnostic channel of that circuit are transmitted back to the originating device. The originating device, then, after transmitting a pattern, will monitor the diagnostic channel to evaluate whether the transmitted packet is in fact received. By monitoring the integrity of the received, loopbacked results, the transmitting device can evaluate the condition of the virtual circuit. In keeping within the description of FIG. 5, a sequence number will typically be utilized for tests in which sequence checking is required. In addition to the errors depicted in FIGS. 6A and 6B, errors could also be diagnosed if the pattern received by the receiving device (FIG. 6A embodiment) did not correlate with the expected pattern. A device on the receiving end will be instructed as to the pattern type and sequence, and thus will know the particular pattern and sequence of data that it expects to receive. It can then monitor the pattern data and sequence received over the diagnostic channel to verify whether that channel is, in fact, properly transmitting data. The accurate reception of data will indicate to the receiving unit that the transmission line defined by the virtual circuit is in good and proper working order. Faulty data will be

an indication that there is some type of error or system fault along or within the virtual

circuit. A loopback test is typically run in conjunction with a send pattern and/monitor

pattern command. When loopback is active on a virtual circuit, all frames received on

the diagnostic channel of that circuit are transmitted back to the originating device).

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta's system/method by incorporating the steps of

identifying parameter values descriptive of the test packets received in the first data

transmission during the observation interval, wherein the parameter values for each test

packet comprise at least one of a serving sector from which the test packet was

received, a sequence number of the test packet, and a length of the test packet; forming

a second data transmission comprising the identified parameter values for test packets

received as suggested by Mawhinney. The motivation is that (as suggested by

Mashinney, column 11 lines 45-60) a device on the receiving end will be instructed as to

the pattern type and sequence, and thus will know the particular pattern and sequence

of data that it expects to receive; It can then monitor the pattern data and sequence

received over the diagnostic channel to verify whether that channel is, in fact, properly

transmitting data; The accurate reception of data will indicate to the receiving unit that

the transmission line defined by the circuit is in good and proper working order; Faulty

data will be an indication that there is some type of error or system fault along or within

the circuit. Known work in one field of endeavor may prompt variations of it for use in

either the same field or a different one based on design incentives or other market

forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Mawhinney do not explicitly teach observation interval for testing.

Brady in the similar field of endeavor teaches in column 4 lines 35-38, relay 48 includes a timer built therein which holds the relay in the loopback position for a predetermined period (interpreted as observation interval) of time during which suitable loopback tests may be performed.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Mawhinney's system/method by incorporating the steps of observation interval for testing as suggested by Brady. The motivation is that such interval limits that time in which tests can be performed leaving open other times for regular operation of the device. Further motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 7, Malmivirta teaches the first channel is a forward traffic channel and the second channel is a reverse traffic channel (abstract).

In regards to claim 8, Malmivirta teaches the second data transmission comprises a plurality of loop back packets, and wherein the loop back packets include the parameter values descriptive of the test packets (column 7 lines 40-45, columns 7-8

lines 58-8, As soon as the G loop has been closed the test equipment can start sending

test data. Testing is preferably carried out such that the test equipment generates test

bursts in which the information bits contain desired "raw data", i.e. bit combinations the

reception of which is to be examined. Functionally, data transmission and reception

occur on the physical protocol level called Layer 1. When the G loop is closed the

mobile station loops in principle the information bits of every burst received on the

downlink data channel back to a certain uplink burst. It is here assumed bursty

transmission. The same principle can easily be generalized to apply to a situation in

which the transmission is continuous; this concerns especially the testing of mobile

stations in systems utilizing the code division multiple access (CDMA) method. In the

exemplary GSM system each burst has 114 information bits to loop back, excluding the

so-called stealing flags. Preferably the loopback does not depend on the contents of the

so-called midamble of the received downlink bursts. In uplink bursts the mobile station

uses the midamble that it would use anyway. The test equipment receives the uplink

bursts sent by the mobile station and demodulates and decrypts them so that the

information bits in a received burst can be processed by the test equipment).

In regards to claims 11 and 25, Malmivirta teaches loop back packet includes a

field indicative of a specific protocol to which the loop back packet belongs (column 7

lines 45-48, functionally, data transmission and reception occur on the physical protocol

level called Layer 1. In principle, the testing need not involve any higher protocol levels

in the mobile station. Therefore inherently loopback packets will have fields indicating

that protocol is a Layer 1 packet protocol).

In regards to claims 12 and 26, Malmivirta does not explicitly teach loop back packet includes a field indicative of a specific packet type for the loop back packet.

Mawhinney in the same or similar field of endeavor teaches loop back packet includes a field indicative of a specific packet type for the loop back packet (figure 5, message type).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of loop back packet includes a field indicative of a specific packet type for the loop back packet as suggested by Mawhinney. The motivation is that (as suggested by Mawhinney, column 11, lines 18-20) the message type is used to indicate the type and disposition of the present frame. For example, whether the test is a pattern test, a connectivity test, a loopback test, etc. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 13, Malmivirta does not explicitly teach loop back packet includes a field indicative of a start of a specific time interval covered by the loop back packet.

Mawhinney in the same or similar field of endeavor teaches loop back packet includes a field indicative of a start of a specific time interval covered by the loop back packet (figure 5, timestamp).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of loop back packet includes a field indicative of a start of a specific time interval covered by the loop back packet as suggested by Mawhinney. The motivation is that (as suggested by Mawhinney, column 12, lines 10-12) a time stamp may be used for certain tests, when, for example, calculating the round trip transmission time. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claims 24 and 27 Malmivirta does not explicitly teach each loop back packet includes a parameter value indicative of omission of one or more test packets.

Mawhinney in the same or similar field of endeavor teaches each loop back packet includes a parameter value indicative of omission of one or more test packets (column 12 lines 32-37, Utilizing the sequence number (i.e. parameter), a transmitting device may look for acknowledgments of the various packets transmitted. If a return/acknowledgment is received out of sequence, the transmitting device will know that intermediate packets were dropped).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of each loop back packet includes a parameter value indicative of omission of one or more test packets as suggested by Mawhinney. The motivation is that (as suggested by

Mawhinney, column 12 lines 32-37) if a return/acknowledgment is received out of sequence, the transmitting device will know that intermediate packets were dropped. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 28, Malmivirta teaches a memory communicatively coupled to a digital signal processing device (DSPD) (column 6 lines 57-59) *receiving a first data transmission comprising test packets of known test data via a first channel* (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test

equipment receives the uplink bursts sent by the mobile station and demodulates and
decrypts them so that the information bits in a received burst can be processed by the
test equipment) *and transmitting the second data transmission via a second channel*
(column 7 lines 58-60, when the G loop is closed the mobile station loops in principle
the information bits of every burst received on the downlink data channel back to a
certain uplink burst).

Malmivirta does not explicitly teach *identifying parameter values descriptive of
the test packets received in the first data transmission, wherein the parameter values for
each test packet comprise at least one of a serving sector from which the test packet
was received, a sequence number of the test packet, and a length of the test packet;
forming a second data transmission comprising the identified parameter values for test
packets received.*

Mawhinney in the similar field of endeavor teaches *identifying parameter values
descriptive of the test packets received in the first data transmission during the
observation interval, wherein the parameter values for each test packet comprise at
least one of a serving sector from which the test packet was received, a sequence
number of the test packet, and a length of the test packet; forming a second data
transmission comprising the identified parameter values for test packets received*
(Figure 5 sequence number field, column 3 lines 38-53, column 11 lines 45-60, lines
column 12 lines 1-15, column 4 lines 44-47, the testing means have a transmitter
means for transmitting the test sequence to the second device across the diagnostic
channel. A receiver is associated with the second device for receiving and <u>identifying</u>

the <u>test sequence</u> transmitted by the first device. Responding means associated with the second device for responding to the test sequence, the responding means being configured to transmit its response over the diagnostic channel, back to the first device. Finally, evaluating means are associated with the first device for identifying the response. The specific operation of the particular elements, such as the responding means and the evaluating means still necessarily vary, depending upon the particular diagnostic test being executed. For example, the operation of the elements, while executing a diagnostic pattern test, will be different than when executing a loopback test. A loopback test is typically run in conjunction with a send pattern and/monitor pattern command. When loopback is active on a virtual circuit, all frames received on the diagnostic channel of that circuit are transmitted back to the originating device. The originating device, then, after transmitting a pattern, will monitor the diagnostic channel to evaluate whether the transmitted packet is in fact received. By monitoring the integrity of the received, loopbacked results, the transmitting device can evaluate the condition of the virtual circuit. In keeping within the description of FIG. 5, a <u>sequence number</u> will typically be utilized for tests in which sequence checking is required. In addition to the errors depicted in FIGS. 6A and 6B, errors could also be diagnosed if the pattern received by the receiving device (FIG. 6A embodiment) did not correlate with the expected pattern. A device on the receiving end will be instructed as to the pattern type and sequence, and thus will know the particular pattern and sequence of data that it expects to receive. It can then monitor the pattern data and sequence received over the diagnostic channel to verify whether that channel is, in fact, properly transmitting data.

The accurate reception of data will indicate to the receiving unit that the transmission

line defined by the virtual circuit is in good and proper working order. Faulty data will be

an indication that there is some type of error or system fault along or within the virtual

circuit. A loopback test is typically run in conjunction with a send pattern and/monitor

pattern command. When loopback is active on a virtual circuit, all frames received on

the diagnostic channel of that circuit are transmitted back to the originating device).

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta's system/method by incorporating the steps of

identifying parameter values descriptive of the test packets received in the first data

transmission during the observation interval, wherein the parameter values for each test

packet comprise at least one of a serving sector from which the test packet was

received, a sequence number of the test packet, and a length of the test packet; forming

a second data transmission comprising the identified parameter values for test packets

received as suggested by Mawhinney. The motivation is that (as suggested by

Mashinney, column 11 lines 45-60) a device on the receiving end will be instructed as to

the pattern type and sequence, and thus will know the particular pattern and sequence

of data that it expects to receive; It can then monitor the pattern data and sequence

received over the diagnostic channel to verify whether that channel is, in fact, properly

transmitting data; The accurate reception of data will indicate to the receiving unit that

the transmission line defined by the circuit is in good and proper working order; Faulty

data will be an indication that there is some type of error or system fault along or within

the circuit. Known work in one field of endeavor may prompt variations of it for use in

either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Mawhinney do not explicitly teach observation interval for testing.

Brady in the similar field of endeavor teaches in column 4 lines 35-38, relay 48 includes a timer built therein which holds the relay in the loopback position for a predetermined period (interpreted as observation interval) of time during which suitable loopback tests may be performed.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Mawhinney's system/method by incorporating the steps of observation interval for testing as suggested by Brady. The motivation is that such interval limits that time in which tests can be performed leaving open other times for regular operation of the device. Further motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

9.   Claims 29-31 and 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Mawhinney et al. (US PAT 5898674, hereinafter Mawhinney), Brady (US PAT

3922508), hereinafter referred to as Brady and Engbersen (US PAT 5271000,

hereinafter Engbersen).

In regards to claim 29, Malmivirta teaches receiving a plurality of test packets of

known test data via a forward traffic channel (column 7 lines 40-45, columns 7-8 lines

58-8, As soon as the G loop has been closed the test equipment can start sending test

data. Testing is preferably carried out such that the test equipment generates test

bursts in which the information bits contain desired "raw data", i.e. bit combinations the

reception of which is to be examined. Functionally, data transmission and reception

occur on the physical protocol level called Layer 1. When the G loop is closed the

mobile station loops in principle the information bits of every burst received on the

downlink data channel (i.e. forward traffic channel) back to a certain uplink burst. It is

here assumed bursty transmission. The same principle can easily be generalized to

apply to a situation in which the transmission is continuous; this concerns especially the

testing of mobile stations in systems utilizing the code division multiple access (CDMA)

method. In the exemplary GSM system each burst has 114 information bits to loop

back, excluding the so-called stealing flags. Preferably the loopback does not depend

on the contents of the so-called midamble of the received downlink bursts. In uplink

bursts the mobile station uses the midamble that it would use anyway. The test

equipment receives the uplink bursts sent by the mobile station and demodulates and

decrypts them so that the information bits in a received burst can be processed by the

test equipment); and transmitting the loop back packets via a reverse traffic channel

(column 7 lines 58-60, when the G loop is closed the mobile station loops in principle

the information bits of every burst received on the downlink data channel back to a certain uplink burst).

Malmivirta does not explicitly teach *identifying parameter values descriptive of the test packets received in the first data transmission, wherein the parameter values for each test packet comprise sequence number of the test packet; forming a second data transmission comprising sequence number for test packets received.*

Mawhinney in the similar field of endeavor teaches *identifying parameter values descriptive of the test packets received in the first data transmission, wherein the parameter values for each test packet comprise sequence number of the test packet; forming a second data transmission comprising sequence number for test packets received* (Figure 5 sequence number field, column 3 lines 38-53, column 11 lines 45-60, lines column 12 lines 1-15, column 4 lines 44-47, the testing means have a transmitter means for transmitting the test sequence to the second device across the diagnostic channel. A receiver is associated with the second device for receiving and identifying the test sequence transmitted by the first device. Responding means associated with the second device for responding to the test sequence, the responding means being configured to transmit its response over the diagnostic channel, back to the first device. Finally, evaluating means are associated with the first device for identifying the response. The specific operation of the particular elements, such as the responding means and the evaluating means still necessarily vary, depending upon the particular diagnostic test being executed. For example, the operation of the elements, while executing a diagnostic pattern test, will be different than when executing a loopback

test. A loopback test is typically run in conjunction with a send pattern and/monitor pattern command. When loopback is active on a virtual circuit, all frames received on the diagnostic channel of that circuit are transmitted back to the originating device. The originating device, then, after transmitting a pattern, will monitor the diagnostic channel to evaluate whether the transmitted packet is in fact received. By monitoring the integrity of the received, loopbacked results, the transmitting device can evaluate the condition of the virtual circuit. In keeping within the description of FIG. 5, a sequence number will typically be utilized for tests in which sequence checking is required. In addition to the errors depicted in FIGS. 6A and 6B, errors could also be diagnosed if the pattern received by the receiving device (FIG. 6A embodiment) did not correlate with the expected pattern. A device on the receiving end will be instructed as to the pattern type and sequence, and thus will know the particular pattern and sequence of data that it expects to receive. It can then monitor the pattern data and sequence received over the diagnostic channel to verify whether that channel is, in fact, properly transmitting data. The accurate reception of data will indicate to the receiving unit that the transmission line defined by the virtual circuit is in good and proper working order. Faulty data will be an indication that there is some type of error or system fault along or within the virtual circuit. A loopback test is typically run in conjunction with a send pattern and/monitor pattern command. When loopback is active on a virtual circuit, all frames received on the diagnostic channel of that circuit are transmitted back to the originating device).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of

identifying parameter values descriptive of the test packets received in the first data
transmission, wherein the parameter values for each test packet comprise sequence
number of the test packet; forming a second data transmission comprising sequence
number for test packets received as suggested by Mawhinney. The motivation is that
(as suggested by Mashinney, column 11 lines 45-60) a device on the receiving end will
be instructed as to the pattern type and sequence, and thus will know the particular
pattern and sequence of data that it expects to receive; It can then monitor the pattern
data and sequence received over the diagnostic channel to verify whether that channel
is, in fact, properly transmitting data; The accurate reception of data will indicate to the
receiving unit that the transmission line defined by the circuit is in good and proper
working order; Faulty data will be an indication that there is some type of error or
system fault along or within the circuit. Known work in one field of endeavor may prompt
variations of it for use in either the same field or a different one based on design
incentives or other market forces/market place incentives if the variations are
predictable to one of ordinary skill in the art.

      Malmivirta and Mawhinney do not explicitly teach observation interval for testing.

      Brady in the similar field of endeavor teaches in column 4 lines 35-38, relay 48
includes a timer built therein which holds the relay in the loopback position for a
predetermined period (interpreted as observation interval) of time during which suitable
loopback tests may be performed.

      It would have been obvious to one having ordinary skill in the art at the time the
invention was made to modify Malmivirta and Mawhinney's system/method by

incorporating the steps of observation interval for testing as suggested by Brady. The motivation is that such interval limits that time in which tests can be performed leaving open other times for regular operation of the device. Further motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta, Mawhinney and Brady do not explicitly teach source address being part of the test packet.

Engbersen teaches (abstract) for detecting errors, the test information would include an input address indicating the source of the test packet, a sequence number defining the order in which the packet should arrive at the destination, time bits relating to the packet length and/or to the expected packet transmission delay, and a cyclic redundancy code which covers the entire contents of the test packet, including its control portion.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Mawhinney and Brady's system/method with the steps of source address being part of the test packet as suggested by Engbersen. The motivation is that such method enables analyzing entity at a receiving station identify the sender accurately and reliably. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design

incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claims 30, 31 and 39, Malmivirta teaches sending a first data transmission via a first channel, wherein the first data transmission comprises test packets of known test data (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined); receiving a second data transmission via a second channel, wherein the second data transmission includes parameter values descriptive of the test packets in the first data transmission received (column 8 lines 5-10, The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment. To compute the bit error ratio (BER) the test equipment compares the received information bits to the raw data it sent to the mobile station). In regards to claim 39, Malmivirta teaches a memory communicatively coupled to a digital signal processing device (DSPD) (column 6 lines 57-59).

Malmivirta does not explicitly teach a record for each test packet correctly received.

Mawhinney in the similar field of endeavor teaches a record for each test packet correctly received (Figure 5 sequence number field, column 3 lines 38-53, column 11 lines 45-60, lines column 12 lines 1-15, column 4 lines 44-47).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of a record for each test packet correctly received as suggested by Mawhinney. The motivation is that (as suggested by Mashinney, column 11 lines 45-60) a device on the receiving end will be instructed as to the pattern type and sequence, and thus will know the particular pattern and sequence of data that it expects to receive; It can then monitor the pattern data and sequence received over the diagnostic channel to verify whether that channel is, in fact, properly transmitting data; The accurate reception of data will indicate to the receiving unit that the transmission line defined by the circuit is in good and proper working order; Faulty data will be an indication that there is some type of error or system fault along or within the circuit. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Mawhinney do not explicitly teach observation interval for testing.

Brady in the similar field of endeavor teaches in column 4 lines 35-38, relay 48 includes a timer built therein which holds the relay in the loopback position for a predetermined period (interpreted as observation interval) of time during which suitable loopback tests may be performed.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Mawhinney's system/method by incorporating the steps of observation interval for testing as suggested by Brady. The

motivation is that such interval limits that time in which tests can be performed leaving open other times for regular operation of the device. Further motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Mawhinney and Brady do not explicitly teach parameter values are configured to be used to update a plurality of variables employable in testing the one or more channels; updating a plurality of variables based on the parameter values included in a second data transmission; and determining a packet error rate based on information included in the second data transmission.

Engbersen teaches (abstract, column 19 lines 17-20) for detecting errors, the test information would include an input address indicating the source of the test packet, a sequence number defining the order in which the packet should arrive at the destination, time bits relating to the packet length and/or to the expected packet transmission delay, and a cyclic redundancy code which covers the entire contents of the test packet, including its control portion. Each analyzer at a receiving station operates autonomously from the senders and processes all received traffic in real-time; this enables it to recognize all defined system errors, even those occurring with very low probability, at the packet level. Based on this information, the transputer either performs statistical computations (e.g. counting of the faulty events) (i.e. interpreted as updating

variables)). Further, regarding packet error rate, Engbersen teaches error detection is performed by analyzing the arriving packets at the output of the assumed fault path for unexpected contents.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Sakakura's system/method with the steps of parameter values are configured to be used to update a plurality of variables employable in testing the one or more channels; updating a plurality of variables based on the parameter values included in a second data transmission; and determining a packet error rate based on information included in the second data transmission as suggested by Engbersen. The motivation is that (as suggested by Engbersen, abstract) such method enables analyzer at a receiving station operates autonomously from the senders and processes all received traffic in real-time; this enables it to recognize all defined system errors, even those occurring with very low probability, at the packet level. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

10.   Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Mawhinney et al. (US PAT 5898674, hereinafter Mawhinney), Brady (US PAT 3922508), hereinafter referred to as Brady and Funk et al. (US PAT 6766164), hereinafter referred to as Funk.

Malmivirta, Mawhinney and Brady teach all the limitations of claim 6 above but do not explicitly teach test packet is formed for each particular time interval.

Funk in the same field of endeavor teaches test packets being formed for particular time interval (column 3 lines 61-67).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Mawhinney and Brady's method by incorporating one loop back packet being formed for each particular time interval as taught by Funk. The motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

11.   Claims 40-44 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of Numminen (US PAT 5802105, hereinafter Tiedemann), Oommen et al. (US PAT 6799203) and Tiedemann et al. (US PAT 5802105, hereinafter Tiedemann).

In regards to claims 40-44 Malmivirta teaches receiving a plurality of test packets via a forward traffic channel (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which

is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment).

In regards to claims 40, 41, 42 and 43 Malmivirta does not explicitly teach collecting data for a first parameter while in idle state and not exchanging data via the link; collecting a second statistic for a second parameter different from the first parameter while in connected state and exchanging data via the link; receiving a first message requesting the first or second statistic, and sending a second message with the requested first or second statistic.

In regards to claims 40, 41, 42 and 43 Numminen teaches a method of collecting data for a first parameter while in idle state and not exchanging data via the link (column 10 lines 1-8, In addition to the testing described above the invention is applicable when

a mobile station or a terminal of a cellular radio system in general is in normal use, i.e.
moving with its user within the area of the cellular radio system. Then it is for most of
the time in the so-called idle mode (i.e. idle state) in which it receives from base stations
certain downlink messages and sends occasionally location update messages (i.e.
collecting data for a first parameter "location area") uplink. The cellular radio system
knows at all times the location of every idling mobile station (i.e. first statistics being
transmitted data of "location area" for every idling mobile station) with the accuracy of a
so-called location area (LA) at least). Numminen teaches collecting a second statistic
for a second parameter different from the first parameter while in connected state and
exchanging data via the link (column 7 lines 46-47 and column 7 lines 59-61, column 9
lines 10-11 and column 8 lines 29-39, while the G loop is active the mobile station
compares the received bit sequence portions to the locally produced portions and
measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the
measurement results in a desired manner. Complete statistics or information elements
representing the reception error status in general are sent uplink to the test equipment.
At first the test equipment sends a comparison and statistical operation start command
associated with the data channel. The mobile station activates the test loop in a certain
time after it has sent the acknowledge). Numminen teaches receiving a first message
requesting the first or second statistic, and sending a second message with the
requested first or second statistic (column 8 lines 29-39, while the G loop is active the
mobile station compares the received bit sequence portions to the locally produced
portions and measures e.g. the bit error ratio or frame erasure ratio and compiles

statistics of the measurement results in a desired manner. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's teaching by incorporating the steps of collecting data for a first parameter while in idle state and not exchanging data via the link; collecting a second statistic for a second parameter different from the first parameter while in connected state and exchanging data via the link; receiving a first message requesting the first or second statistic, and sending a second message with the requested first or second statistic as suggested by Numminen. The motivation is that by collecting statistics real-time while testing is being performed enables a reliable and up-to-date statistic collection process to check network reliability. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claims 40-43 Numminen does not explicitly teach, collecting statistics during each of the transactions.

Oommen in the same field of endeavor teaches (column 2 lines 46-49) OTAMD involves requesting statistics and performing diagnostic tests in the MS using a command issued from the network for testing purpose.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's teaching by incorporating the statistic

gathering during transactions as taught by Oommen. The motivation is that by collecting statistics real-time while testing is being performed enables a reliable and up-to-date statistic collection process to check network reliability. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claims 40 and 44, Malmivirta, Numminen and Oommen do not explicitly teach collecting the first statistic occurs while performing testing.

Tiedemann in the same field of endeavor teaches collecting the first statistic occurs while performing testing function (column 14 lines 40-57).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Numminen and Oommen's teaching by incorporating the steps of collecting the first statistic occurs while performing testing as taught by Oommen. The motivation is that by collecting statistics real-time while testing is being performed enables a reliable and up-to-date statistic collection process to check network reliability. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 44, Malmivirta teaches a memory communicatively coupled to a digital signal processing device (DSPD) (column 6 lines 57-59).

12.   Claims 45 and 56, are rejected under 35 U.S.C. 103(a) as being unpatentable

over Malmivirta et al. (US PAT 6680913), hereinafter referred to as Malmivirta in view of

Tiedemann.

        In regards to claim 45 and 56 Malmivirta teaches receiving a plurality of test

packets via a forward traffic channel (column 7 lines 40-45, columns 7-8 lines 58-8, As

soon as the G loop has been closed the test equipment can start sending test data.

Testing is preferably carried out such that the test equipment generates test bursts in

which the information bits contain desired "raw data", i.e. bit combinations the reception

of which is to be examined. Functionally, data transmission and reception occur on the

physical protocol level called Layer 1. When the G loop is closed the mobile station

loops in principle the information bits of every burst received on the downlink data

channel back to a certain uplink burst. It is here assumed bursty transmission. The

same principle can easily be generalized to apply to a situation in which the

transmission is continuous; this concerns especially the testing of mobile stations in

systems utilizing the code division multiple access (CDMA) method. In the exemplary

GSM system each burst has 114 information bits to loop back, excluding the so-called

stealing flags. Preferably the loopback does not depend on the contents of the so-called

midamble of the received downlink bursts. In uplink bursts the mobile station uses the

midamble that it would use anyway. The test equipment receives the uplink bursts sent

by the mobile station and demodulates and decrypts them so that the information bits in

a received burst can be processed by the test equipment).

Malmivirta does not explicitly teach selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel. Malmivirta does not explicitly teach the plurality of test packets comprising information for a plurality of rates being tested for the traffic channel.

Tiedemann in the same field of endeavor teaches the system allows the test sequence of digital data to be transmitted at one of a set of known data rates, with the receive station being disposed to identify the data rate associated with each test sequence of digital data. In a preferred implementation transmission of the test sequence involves generating a first plurality of data packets, which collectively comprise the test sequence of digital data. Each data packet is assigned one of a multiplicity of data rates in accordance with a first pseudorandom process, and is then transmitted at the data rate assigned thereto (abstract). Tiedemann in the same field of endeavor teaches plurality of test packets comprising information for a plurality of rates being tested for the traffic channel (column 9 lines 30-33 and TABLE II, Referring now to TABLE II, there are listed the number of bits included within the sequences comprising a set of exemplary data packets transmitted at various data rates).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's teaching by incorporating the steps of selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel. The motivation is that The motivation is that by testing communication link at various data

rates a node can get an accurate picture of the current condition of the link; thus enabling it to modify, most efficiently and reliably, link parameters related to rates to enable seamless communication. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

13.   Claim 49 is rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta and Tiedemann as applied to claim 45 above and further in view of Numminen.

        In regards to claim 49 Malmivirta and Tiedemann teach a testing system as described in the rejections of claim 45 above.

        Malmivirta and Tiedemann do not explicitly teach of message includes an indication of maintenance of a test mode on the traffic channel in event of a connection closure or a lost connection.

        Numminen in the same or similar field of endeavor teaches message includes an indication of maintenance of a test mode on the traffic channel in event of a connection closure or a lost connection (column 7 lines 18-20, So test mode means that the mobile station to be tested is instructed to maintain a connection' on a certain transmission channel. The mobile station is kept in the test mode by Layer 3 signaling).

        It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Tiedemann's teaching by incorporating

message includes an indication of maintenance of a test mode on the traffic channel in event of a connection closure or a lost connection as suggested by Numminen. The motivation is that such method enables a system to designate and maintain a non-used channel for testing purpose; thus making efficient use of the channel resources. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

14.   Claims 50-53 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta and Tiedemann as applied to claim 45 above and further in view of Kobayasi.

In regards to claims 50-52 Malmivirta and Tiedemann teaches a testing system as described in the rejections of claim 45 above.

In regards to claims 50-52 Malmivirta and Tiedemann do not explicitly teach of having protocol type, packet type, number of records field, time interval, source address, sequence number in the test packet. In regards to claim 58 Malmivirta does not explicitly teach a queue for the test packets.

In regards to claims 50 and 51 Kobayasi discloses protocol type, packet type, number of records field, time interval, source address, sequence number in the packets shown in FIGS. 582 through 628. In regards to claim 52 Kobayasi teaches (column 3 lines 5-10) that since the source SW station 3 and the terminal SW station 6 mark the time stamp onto the payload field of the packet, the OS center 1 is informed of the

transmission time of packets according to the information. In regards to claim 58, 62

and 65 Kobayasi teaches buffers (fig 132) for data packets.

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta and Tiedemann's teaching by incorporating

the loopback test scheme as taught by Kobayasi. The motivation is that (as suggested

by Kobayasi column 317 lines 29-34) the present invention realizes an efficient test

within a short time by performing a test cell loopback check, which has been made in a

test device, through a test program in the switch. Additionally, transmitting cell data

from a test device requires no testing units because the loopback jig can replace the

testing units. Known work in one field of endeavor may prompt variations of it for use in

either the same field or a different one based on design incentives or other market

forces/market place incentives if the variations are predictable to one of ordinary skill in

the art.

In regards to claim 53, Malmivirta and Tiedemann do not explicitly teach field

indicative of whether any loop back packets were lost due to buffer overflow.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test

being started by issuing a test connectionless packet transmission request message

(test start request) from the OS center 1 to SW station 3. The request message

contains an identification information ID indicating terminal SW station 6. SW station 3

generates a test packet with the identification address of terminal SW station 6 set as its

destination address DA and the identification address of its home station (SW station 3)

set as its source address SA. The test packet is output to terminal SW station 6. In SW

stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG. 783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Tiedemann's system/method by incorporating the steps of having source id and sequence number in test packets as taught by Kobayasi. The motivation is that having a source and sequence number enables a system to easily and efficiently identify the source of the test packets and number of packets received or lost due to overflow for statistical record keeping. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

15.   Claims 46-48 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta and Tiedmann as applied to claim 45 above, and further in view of Ikeda (US PAT 5636212).

In regards to claims 46 and 47 Malmivirta and Tiedmann teach a method for testing one or more channels in a wireless data communication system as described in the rejections of claim 45 above.

Malmivirta and Tiedmann do not explicitly teach message having maximum and minimum rate for rate selection.

Ikeda in the same field of endeavor teaches (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Tiedmann's system/method by incorporating the concept of sending maximum band-width and a minimum band-width via message as taught by Ikeda. The motivation is that (as suggested by Ikeda, column 2 lines 5-10) to provide a flexible method of reserving a band-width for a burst capable of flexibly reserving a band-width according to a maximum band-width and a minimum band-width requested for reservation. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 48, Malmivirta and Tiedmann do not explicitly teach with the steps of the selected rates for the test packets being further limited by a maximum rate specified by a media access control (MAC) protocol

It would have been obvious of one of ordinary skill in the art at the time of invention to modify Malmivirta and Tiedmann's system/method with the steps of the

selected rates for the test packets being further limited by a maximum rate specified by a media access control (MAC) protocol; as a link defined to have a maximum bandwidth rate cannot operate in a higher bandwidth which may cause overflow of data in buffers and in result cause loss of packets. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

16.   Claims 57 and 58, are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta, in view of Tiedemann, Kobayasi, Ikeda and and Sjoblom (US PAT PUB 2002/0009053).

        In regards to claim 57 and 58 Malmivirta teaches receiving a plurality of test packets via a forward traffic channel (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in

systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment).

Malmivirta does not explicitly teach selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel.

Tiedemann in the same field of endeavor teaches the system allows the test sequence of digital data to be transmitted at one of a set of known data rates, with the receive station being disposed to identify the data rate associated with each test sequence of digital data. In a preferred implementation transmission of the test sequence involves generating a first plurality of data packets, which collectively comprise the test sequence of digital data. Each data packet is assigned one of a multiplicity of data rates in accordance with a first pseudorandom process, and is then transmitted at the data rate assigned thereto (abstract).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's teaching by incorporating the steps of selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel. The

motivation is that The motivation is that by testing communication link at various data rates a node can get an accurate picture of the current condition of the link; thus enabling it to modify, most efficiently and reliably, link parameters related to rates to enable seamless communication. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Tiedemann do not explicitly teach identifying a transmission source of each received test packet; wherein packet includes the transmission source of each covered test packet. Malmivirta and Tiedemann do not explicitly teach selecting rates for the test packets based on a rate selection scheme. In regards to claim 58 Malmivirta does not explicitly teach a queue for the test packets.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3 generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW

station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi teaches (column 97 lines 45-46) Loopback of a test cell is done in a 156 Mbps cell highway. Kobayasi discloses protocol type, packet type, number of records field, time interval, source address, sequence number in the packets shown in FIGS. 582 through 628. Kobayasi teaches (column 3 lines 5-10) that since the source SW station 3 and the terminal SW station 6 mark the time stamp onto the payload field of the packet, the OS center 1 is informed of the transmission time of packets according to the information.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's teaching by incorporating the loopback test scheme as taught by Kobayasi. The motivation is that (as suggested by Kobayasi column 317 lines 29-34) the present invention realizes an efficient test within a short time by performing a test cell loopback check, which has been made in a test device, through a test program in the switch. Additionally, transmitting cell data from a test device requires no testing units because the loopback can replace the testing units. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 57 Malmivirta, Tiedemann and Kobayasi do not explicitly teach message having maximum and minimum rate for rate selection.

Ikeda in the same field of endeavor teaches (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Tiedemann and Kobayasi's system/method by incorporating the concept of sending maximum band-width and a minimum band-width via message as taught by Ikeda. The motivation is that (as suggested by Ikeda, column 2 lines 5-10) to provide a flexible method of reserving a band-width for a burst capable of flexibly reserving a band-width according to a maximum band-width and a minimum band-width requested for reservation. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta, Tiedemann, Kobayasi and Ikeda do not explicitly teach identifying sequence number in test packets and forming test packets including the sequence number.

Sjoblom in the same field of endeavor teaches identifying sequence number in test packets and forming test packets including the sequence number (paragraphs 0023 and 0026).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Tiedemann, Kobayasi and Ikeda's teaching by incorporating the steps of identifying sequence number in test packets and forming test packets including the sequence number as suggested by Sjoblom. The motivation is that the sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted; thus enabling a

reliable communication. Known work in one field of endeavor may prompt variations of it

for use in either the same field or a different one based on design incentives or other

market forces/market place incentives if the variations are predictable to one of ordinary

skill in the art.

17.   Claim 59 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Malmivirta in view of Tiedemann.

        In regards to claim 59 Malmivirta teaches sending a first message having

included therein test settings selected for the reverse traffic channel (column 7 lines 40-

45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment

can start sending test data. Testing is preferably carried out such that the test

equipment generates test bursts in which the information bits contain desired "raw

data", i.e. bit combinations the reception of which is to be examined. Functionally, data

transmission and reception occur on the physical protocol level called Layer 1. When

the G loop is closed the mobile station loops in principle the information bits of every

burst received on the downlink data channel back to a certain uplink burst. It is here

assumed bursty transmission. The same principle can easily be generalized to apply to

a situation in which the transmission is continuous; this concerns especially the testing

of mobile stations in systems utilizing the code division multiple access (CDMA)

method. In the exemplary GSM system each burst has 114 information bits to loop

back, excluding the so-called stealing flags. Preferably the loopback does not depend

on the contents of the so-called midamble of the received downlink bursts. In uplink

bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment); receiving a plurality of test packets on the traffic channel and determining a packet error based on information included in plurality of test packets (column 7 lines 58-60, column 8 lines 5-15, when the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment. To compute the bit error ratio (BER) the test equipment compares the received information bits to the raw data it sent to the mobile station. The signal level at which the downlink bursts are delivered to the terminal equipment is variable so that the bit error ratio observed by the test equipment describes the sensitivity of the receiver in the mobile station especially at low signal levels).

Malmivirta does not explicitly teach receiving a plurality of test packets, the plurality of test packets comprising information for plurality of rates being tested and updating a plurality of variables maintained for a plurality of rates based on the rates of the received test packets. Malmivirta does not explicitly teach determining a packet error based on the information included in plurality of test packets for the plurality of rates.

Tiedemann in the same field of endeavor teaches updating a plurality of variables maintained for the plurality of rates based on the rates of the received test packets (column 14 lines 40-57). Tiedemann in the same field of endeavor teaches receiving a plurality of test packets at a plurality of rates (abstract, Each data packet is assigned one of a multiplicity of data rates in accordance with a first pseudorandom process, and is then transmitted at the data rate assigned thereto), the plurality of test packets comprising information for plurality of rates being tested (column 9 lines 30-33 and TABLE II, Referring now to TABLE II, there are listed the number of bits included within the sequences comprising a set of exemplary data packets transmitted at various data rates). Tiedemann in the same field of endeavor teaches determining a packet error based on the information included in plurality of test packets for the plurality of rates (column 10 lines 36-44, Subsequent to identification of the data rate associated with a particular received frame, the test data replication circuit 50 supplies a locally-generated packet of test data of the appropriate type to the digital comparator 49. Specifically, a frame category indicative of either a Rate 1, Rate 1/2, Rate 1/4, Rate 1/8, Blank, Rate 1 with Bit Error or an Insufficient Frame Quality is provided by the circuit 50 to comparator 49).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's system/method by incorporating the steps of receiving a plurality of test packets at a plurality of rates, the plurality of test packets comprising information for plurality of rates being tested and updating a plurality of variables maintained for the plurality of rates based on the rates of the received test

packets and determining a packet error based on the information included in plurality of

test packets for the plurality of rates as suggested by Tiedemann. The motivation is that

by updating various variables related to communication link status, a node keeps an up-

to-date information of the current condition of the links; thus enabling it to modify, most

efficiently and reliably, link parameters to enable seamless communication. Further

motivation is that by testing communication link at various data rates a node can get an

accurate picture of the current condition of the link; thus enabling it to modify, most

efficiently and reliably, link parameters related to rates to enable seamless

communication. Known work in one field of endeavor may prompt variations of it for use

in either the same field or a different one based on design incentives or other market

forces/market place incentives if the variations are predictable to one of ordinary skill in

the art.

18.   Claim 60 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Malmivirta and Tiedemann in view of Engbersen (US PAT 5271000, hereinafter

Engbersen).

        In regards to claim 60, Malmivirta and Tiedemann teach all the limitations of

claim 59 above but do not explicitly teach updating a first variable based on a sequence

number of the test packet.

        Engbersen teaches (abstract, column 19 lines 17-20) for detecting errors, the test

information would include an input address indicating the source of the test packet, a

sequence number defining the order in which the packet should arrive at the

destination, time bits relating to the packet length and/or to the expected packet transmission delay, and a cyclic redundancy code which covers the entire contents of the test packet, including its control portion. Each analyzer at a receiving station operates autonomously from the senders and processes all received traffic in real-time; this enables it to recognize all defined system errors, even those occurring with very low probability, at the packet level. Based on this information, the transputer either performs statistical computations (e.g. counting of the faulty events) (i.e. interpreted as updating varibles)). Further, regarding packet error rate, Engbersen teaches error detection is performed by analyzing the arriving packets at the output of the assumed fault path for unexpected contents.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Tiedemann's system/method with the steps of updating a first variable based on a sequence number of the test packet as suggested by Engbersen. The motivation is that such method enables a receiver to recognize all defined transmission errors and calculate for further analysis. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

19.   Claims 61-63, 65, 67 and 68 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta, in view of Kobayasi et al. (US PAT 6333932), hereinafter referred to as Kobayasi, Sjoblom (US PAT PUB 2002/0009053) and Brady.

In regards to claims 61-63, 67 and 68 Malmivirta teaches receiving a plurality of test packets of known test data via a forward traffic channel, forming a plurality of loop back packets for the plurality of received test packets, wherein each loop back packet covers zero or more test packets (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment); and transmitting the loop back packets via reverse traffic channel (column 7 lines 58-60, when the G loop is closed the mobile station loops in principle the information bits of every burst received

on the downlink data channel back to a certain uplink burst). In regards to claims 63, 67

and 68 Malmivirta further teaches data transmission comprises data for determining a

packet error (column 8 lines 5-10, The test equipment receives the uplink bursts sent by

the mobile station and demodulates and decrypts them so that the information bits in a

received burst can be processed by the test equipment. To compute the bit error ratio

(BER) the test equipment compares the received information bits to the raw data it sent

to the mobile station).

Malmivirta does not explicitly teach identifying a transmission source of each

received packet; includes the transmission source of each covered test packet and

forming a plurality of loop back packets includes the source number of each covered

test packet. In regards to claim 62 and 65 Malmivirta does not explicitly teach a queue

for the test packets.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test

being started by issuing a test connectionless packet transmission request message

(test start request) from the OS center 1 to SW station 3. The request message

contains an identification information ID indicating terminal SW station 6. SW station 3

generates a test packet with the identification address of terminal SW station 6 set as its

destination address DA and the identification address of its home station (SW station 3)

set as its source address SA. The test packet is output to terminal SW station 6. In SW

stations 4 and 5, test packets are processed as normal packets and transferred to

terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the

packet with its DA and SA inverted. That is, the packet is returned from terminal SW

station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the

packet at the source SW station 3. Kobayasi teaches (column 97 lines 45-46) Loopback

of a test cell is done in a 156 Mbps cell highway. In regards to claims 62 and 65

Kobayasi teaches buffers (fig 132) for data packets.

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta's teaching by incorporating the loopback test

scheme as taught by Kobayasi. The motivation is that (as suggested by Kobayasi

column 317 lines 29-34) the present invention realizes an efficient test within a short

time by performing a test cell loopback check, which has been made in a test device,

through a test program in the switch. Additionally, transmitting cell data from a test

device requires no testing units because the loopback jig can replace the testing units.

Known work in one field of endeavor may prompt variations of it for use in either the

same field or a different one based on design incentives or other market forces/market

place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Kobayasi do not explicitly teach identifying sequence number in

test packets and forming test packets including the sequence number.

Sjoblom in the same field of endeavor teaches identifying sequence number in

test packets and forming test packets including the sequence number (paragraphs 0023

and 0026).

It would have been obvious to one having ordinary skill in the art at the time the

invention was made to modify Malmivirta and Kobayasi's teaching by incorporating the

steps of identifying sequence number in test packets and forming test packets including

the sequence number as suggested by Sjoblom. The motivation is that the sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted; thus enabling a reliable communication. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Kobayasi do not explicitly teach observation interval for testing.

Brady in the similar field of endeavor teaches in column 4 lines 35-38, relay 48 includes a timer built therein which holds the relay in the loopback position for a predetermined period (interpreted as observation interval) of time during which suitable loopback tests may be performed.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Kobayasi's system/method by incorporating the steps of observation interval for testing as suggested by Brady. The motivation is that such interval limits that time in which tests can be performed leaving open other times for regular operation of the device. Further motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claims 61 and 67 Malmivirta teaches a receive data processor (figure 3 elements 303 and 304 combined), a transmit data processor (figure 3 elements 310 and 311 combined) and a controller (figure 3 element 307).

20.   Claims 64 and 66 are rejected under 35 U.S.C. 103(a) as being unpatentable over Malmivirta, in view of Tiedemann, Kobayasi, ikeda and and Sjoblom (US PAT PUB 2002/0009053).

In regards to claim 64 and 66 Malmivirta teaches receiving a plurality of test packets via a forward traffic channel (column 7 lines 40-45, columns 7-8 lines 58-8, As soon as the G loop has been closed the test equipment can start sending test data. Testing is preferably carried out such that the test equipment generates test bursts in which the information bits contain desired "raw data", i.e. bit combinations the reception of which is to be examined. Functionally, data transmission and reception occur on the physical protocol level called Layer 1. When the G loop is closed the mobile station loops in principle the information bits of every burst received on the downlink data channel back to a certain uplink burst. It is here assumed bursty transmission. The same principle can easily be generalized to apply to a situation in which the transmission is continuous; this concerns especially the testing of mobile stations in systems utilizing the code division multiple access (CDMA) method. In the exemplary GSM system each burst has 114 information bits to loop back, excluding the so-called stealing flags. Preferably the loopback does not depend on the contents of the so-called midamble of the received downlink bursts. In uplink bursts the mobile station uses the

midamble that it would use anyway. The test equipment receives the uplink bursts sent by the mobile station and demodulates and decrypts them so that the information bits in a received burst can be processed by the test equipment).

Malmivirta does not explicitly teach selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel.

Tiedemann in the same field of endeavor teaches the system allows the test sequence of digital data to be transmitted at one of a set of known data rates, with the receive station being disposed to identify the data rate associated with each test sequence of digital data. In a preferred implementation transmission of the test sequence involves generating a first plurality of data packets, which collectively comprise the test sequence of digital data. Each data packet is assigned one of a multiplicity of data rates in accordance with a first pseudorandom process, and is then transmitted at the data rate assigned thereto (abstract).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta's teaching by incorporating the steps of selecting rates for the test packets based on a set of rules for rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel as suggested by Tiedemann. The motivation is that The motivation is that by testing communication link at various data rates a node can get an accurate picture of the current condition of the link; thus enabling it to modify, most efficiently and reliably, link parameters related to rates to enable seamless communication. Known work in one

field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta and Tiedemann do not explicitly teach test packets having transmission source.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3 generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta and Tiedemann's system/method by incorporating the steps of having source id in test packets as taught by Kobayasi. The motivation is that having a source and sequence number enables a system to easily and efficiently identify the source of the test packets and number of packets received for

statistical record keeping. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta, Tiedemann and Kobayasi does not explicitly teach message having maximum and minimum rate for rate selection

Ikeda in the same field of endeavor teaches (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Tiedemann and Kobayasi's system/method by incorporating the concept of sending maximum band-width and a minimum band-width via message as taught by Ikeda. The motivation is that (as suggested by Ikeda, column 2 lines 5-10) to provide a flexible method of reserving a band-width for a burst capable of flexibly reserving a band-width according to a maximum band-width and a minimum band-width requested for reservation. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

Malmivirta, Tiedemann, Kobayasi and Ikeda do not explicitly teach identifying sequence number in test packets and forming test packets including the sequence number.

Sjoblom in the same field of endeavor teaches identifying sequence number in test packets and forming test packets including the sequence number (paragraphs 0023 and 0026).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Malmivirta, Tiedemann, Kobayasi and Ikeda's teaching by incorporating the steps of identifying sequence number in test packets and forming test packets including the sequence number as suggested by Sjoblom. The motivation is that the sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted; thus enabling a reliable communication. Known work in one field of endeavor may prompt variations of it for use in either the same field or a different one based on design incentives or other market forces/market place incentives if the variations are predictable to one of ordinary skill in the art.

In regards to claim 64 Malmivirta teaches a receive data processor (figure 3 elements 303 and 304 combined), a transmit data processor (figure 3 elements 310 and 311 combined) and a controller (figure 3 element 307).

Allowable Subject Matter

21.   Claims 14-23, 54 and 55 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Response to Arguments

22.   Applicant's arguments see pages 17-33 of the Remarks section, filed 9/14/2009,

with respect to the rejections of the claims have been fully considered, but in view of

<u>further consideration, review and updated search</u> a new ground of rejection is presented

in this office action. As such any further response to Applicant's argument is moot.

        In response to applicant's argument that the examiner has combined an

excessive number of references, reliance on a large number of references in a rejection

does not, without more, weigh against the obviousness of the claimed invention. See In

re Gorman, 933 F.2d 982, 18 USPQ2d 1885 (Fed. Cir. 1991).

Examiner's Note: Examiner has cited particular columns, line numbers and/or

paragraphs in the references applied to the claims above for the convenience of the

applicant. Although the specified citations are representative of the teachings of the art

and are applied to specific limitations within the individual claim, other passages and

figures may apply as well. It is respectfully requested from the applicant in preparing

responses, to fully consider the references in entirety as potentially teaching all or part

of the claimed invention, as well as the context of the passage as taught by the prior art

or disclosed by the Examiner.

Conclusion

23.   Any inquiry concerning this communication or earlier communications from the

examiner should be directed to SALMAN AHMED whose telephone number is

(571)272-8307. The examiner can normally be reached on 9:00 am - 5:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ayaz Sheikh can be reached on (571)272-3795. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Salman Ahmed/

Primary Examiner, Art Unit 2476